




ROBERT STĘPIEŃ
HURTOWNIA CZĘŚCI ELEKTRONICZNYCH
podzespoly-elektroniczne.pl

Tyrystor 2N6509G (25A/800V) TO220 LITTELFUSE RoHS



Dane techniczne:

Nazwa: 2N6509G

Typ: Tyrystor

Napięcie wsteczne: 800V

Prąd przewodzenia: 25A

Prąd bramki: 9mA

Obudowa: TO220

Producent: LITTELFUSE

www.podzespoly-elektroniczne.pl

Robert Stępień Hurtownia Części Elektronicznych; Adres: ul. Wolumen 2, pawilon 71; 01-912 Warszawa; tel.: 601 296 402 /
sklep@podzespoly-elektroniczne.pl

2N6504 Series

Preferred Device

Silicon Controlled Rectifiers

Reverse Blocking Thyristors

Designed primarily for half-wave ac control applications, such as motor controls, heating controls and power supply crowbar circuits.

Features


- Glass Passivated Junctions with Center Gate Fire for Greater Parameter Uniformity and Stability
- Small, Rugged, Thermowatt Constructed for Low Thermal Resistance, High Heat Dissipation and Durability
- Blocking Voltage to 800 Volts
- 300 A Surge Current Capability
- Pb-Free Packages are Available*



ON Semiconductor®

<http://onsemi.com>

SCRs
25 AMPERES RMS
50 thru 800 VOLTS



PIN ASSIGNMENT

| | PIN ASSIGNMENT |
|---|----------------|
| 1 | Cathode |
| 2 | Anode |
| 3 | Gate |
| 4 | Anode |

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

Preferred devices are recommended choices for future use and best overall value.

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

2N6504 Series

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

| Rating | Symbol | Value | Unit |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|--------------------------------|------|
| *Peak Repetitive Off-State Voltage (Note 1) (Gate Open, Sine Wave 50 to 60 Hz, T _J = 25 to 125°C) 2N6504 2N6505 2N6507 2N6508 2N6509 | V _{DRM} , V _{RRM} | 50 100 400 600 800 | V |
| On-State Current RMS (180° Conduction Angles; T _C = 85°C) | I _{T(RMS)} | 25 | A |
| Average On-State Current (180° Conduction Angles; T _C = 85°C) | I _{T(AV)} | 16 | A |
| Peak Non-repetitive Surge Current (1/2 Cycle, Sine Wave 60 Hz, T _J = 100°C) | I _{TSM} | 250 | A |
| Forward Peak Gate Power (Pulse Width ≤ 1.0 μs, T _C = 85°C) | P _{GM} | 20 | W |
| Forward Average Gate Power (t = 8.3 ms, T _C = 85°C) | P _{G(AV)} | 0.5 | W |
| Forward Peak Gate Current (Pulse Width ≤ 1.0 μs, T _C = 85°C) | I _{GM} | 2.0 | A |
| Operating Junction Temperature Range | T _J | −40 to +125 | °C |
| Storage Temperature Range | T _{stg} | −40 to +150 | °C |

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

1. V_{DRM} and V_{RRM} for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

THERMAL CHARACTERISTICS

| Characteristic | Symbol | Max | Unit |
|----------------------------------------------------------------------------------|------------------|-----|------|
| *Thermal Resistance, Junction-to-Case | R _{θJC} | 1.5 | °C/W |
| *Maximum Lead Temperature for Soldering Purposes 1/8 in from Case for 10 Seconds | T _L | 260 | °C |

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted.)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|----------------|--------|-----|-----|-----|------|
|----------------|--------|-----|-----|-----|------|

OFF CHARACTERISTICS

| | | | | | |
|------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|---|---|-----------|----------|
| *Peak Repetitive Forward or Reverse Blocking Current (V _{AK} = Rated V _{DRM} or V _{RRM} , Gate Open) | I _{DRM} , I _{RRM} | − | − | 10 2.0 | μA mA |
| T _J = 25°C | | | | | |
| T _J = 125°C | | − | − | | |

ON CHARACTERISTICS

| | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----|---------------|-------------|----|
| *Forward On-State Voltage (Note 2) (I _{TM} = 50 A) | V _{TM} | − | − | 1.8 | V |
| *Gate Trigger Current (Continuous dc) (V _{AK} = 12 Vdc, R _L = 100 Ω) | I _{GT} | − | 9.0 − | 30 75 | mA |
| T _C = 25°C | | | | | |
| T _C = −40°C | | − | − | | |
| *Gate Trigger Voltage (Continuous dc) (V _{AK} = 12 Vdc, R _L = 100 Ω, T _C = −40°C) | V _{GT} | − | 1.0 | 1.5 | V |
| Gate Non-Trigger Voltage (V _{AK} = 12 Vdc, R _L = 100 Ω, T _J = 125°C) | V _{GD} | 0.2 | − | − | V |
| *Holding Current (V _{AK} = 12 Vdc, Initiating Current = 200 mA, Gate Open) | I _H | − | 18 − | 40 80 | mA |
| T _C = 25°C | | | | | |
| T _C = −40°C | | − | − | | |
| *Turn-On Time (I _{TM} = 25 A, I _{GT} = 50 mAdc) | t _{gt} | − | 1.5 | 2.0 | μs |
| Turn-Off Time (V _{DRM} = rated voltage) (I _{TM} = 25 A, I _R = 25 A) (I _{TM} = 25 A, I _R = 25 A, T _J = 125°C) | t _q | − | 15 − 35 | − − − | μs |

DYNAMIC CHARACTERISTICS

| | | | | | |
|-------------------------------------------------------------------------------------------------------|-------|---|----|---|------|
| Critical Rate of Rise of Off-State Voltage (Gate Open, Rated V _{DRM} , Exponential Waveform) | dv/dt | − | 50 | − | V/μs |
|-------------------------------------------------------------------------------------------------------|-------|---|----|---|------|

*Indicates JEDEC Registered Data.

2. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.

2N6504 Series

Voltage Current Characteristic of SCR

| Symbol | Parameter |
|-----------|-------------------------------------------|
| V_{DRM} | Peak Repetitive Off State Forward Voltage |
| I_{DRM} | Peak Forward Blocking Current |
| V_{RRM} | Peak Repetitive Off State Reverse Voltage |
| I_{RRM} | Peak Reverse Blocking Current |
| V_{TM} | Peak On State Voltage |
| I_H | Holding Current |





Figure 1. Average Current Derating




Figure 2. Maximum On-State Power Dissipation

2N6504 Series




Figure 3. Typical On-State Characteristics




Figure 4. Maximum Non-Repetitive Surge Current






Figure 5. Thermal Response

2N6504 Series


TYPICAL TRIGGER CHARACTERISTICS



**Figure 6. Typical Gate Trigger Current
versus Junction Temperature**



**Figure 7. Typical Gate Trigger Voltage
versus Junction Temperature**



**Figure 8. Typical Holding Current
versus Junction Temperature**

2N6504 Series


ORDERING INFORMATION

| Device | Package | Shipping |
|----------|-----------------------|-----------------|
| 2N6504 | TO-220AB | 500 Units / Box |
| 2N6504G | TO-220AB (Pb-Free) | |
| 2N6505 | TO-220AB | |
| 2N6505G | TO-220AB (Pb-Free) | |
| 2N6505T | TO-220AB | |
| 2N6505TG | TO-220AB (Pb-Free) | |
| 2N6507 | TO-220AB | |
| 2N6507G | TO-220AB (Pb-Free) | |
| 2N6507T | TO-220AB | |
| 2N6507TG | TO-220AB (Pb-Free) | |
| 2N6508 | TO-220AB | |
| 2N6508G | TO-220AB (Pb-Free) | |
| 2N6509 | TO-220AB | |
| 2N6509G | TO-220AB (Pb-Free) | |
| 2N6509T | TO-220AB | |
| 2N6509TG | TO-220AB (Pb-Free) | |

2N6504 Series

PACKAGE DIMENSIONS

TO-220AB
CASE 221A-09
ISSUE AA




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

| DIM | INCHES | | MILLIMETERS | |
|-----|--------|-------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 0.570 | 0.620 | 14.48 | 15.75 |
| B | 0.380 | 0.405 | 9.66 | 10.28 |
| C | 0.160 | 0.190 | 4.07 | 4.82 |
| D | 0.025 | 0.035 | 0.64 | 0.88 |
| F | 0.142 | 0.147 | 3.61 | 3.73 |
| G | 0.095 | 0.105 | 2.42 | 2.66 |
| H | 0.110 | 0.155 | 2.80 | 3.93 |
| J | 0.018 | 0.025 | 0.46 | 0.64 |
| K | 0.500 | 0.562 | 12.70 | 14.27 |
| L | 0.045 | 0.060 | 1.15 | 1.52 |
| N | 0.190 | 0.210 | 4.83 | 5.33 |
| Q | 0.100 | 0.120 | 2.54 | 3.04 |
| R | 0.080 | 0.110 | 2.04 | 2.79 |
| S | 0.045 | 0.055 | 1.15 | 1.39 |
| T | 0.235 | 0.255 | 5.97 | 6.47 |
| U | 0.000 | 0.050 | 0.00 | 1.27 |
| V | 0.045 | --- | 1.15 | --- |
| Z | --- | 0.080 | --- | 2.04 |

STYLE 3:

- PIN 1. CATHODE
2. ANODE
3. GATE
4. ANODE

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your
local Sales Representative.