



ROBERT STĘPIEŃ  
HURTOWNIA CZĘŚCI ELEKTRONICZNYCH  
podzespoly-elektroniczne.pl

# Mostek DF10S (1A/1000V) R=5mm SMD DB107S RoHS



## Dane techniczne:

Nazwa: DF10S

Typ elementu półprzewodnikowego: mostek prostowniczy

Napięcie wsteczne maksymalne: 1000V

Prąd przewodzenia: 1A

Montaż elektryczny: SMD


[www.podzespoly-elektroniczne.pl](http://www.podzespoly-elektroniczne.pl)

Robert Stępień Hurtownia Części Elektronicznych; Adres: ul. Wolumen 2, pawilon 71; 01-912 Warszawa; tel.: 601 296 402 /  
sklep@podzespoly-elektroniczne.pl




## Miniature Glass Passivated Single-Phase Surface Mount Bridge Rectifiers

Case Style DFS

Reverse Voltage 50 to 1000V  
Forward Current 1.0A

Mounting Pad Layout



### Mechanical Data

**Case:** Molded plastic body over passivated junctions**Terminals:** Plated leads solderable per MIL-STD-750, Method 2026**Polarity:** Polarity symbols marked on body**Mounting Position:** Any **Weight:** 0.014 oz., 0.4 g**Packaging codes/options:**

27/1.5K per 13" Reel (16mm Tape)

45/50 ea. per Tube-Bulk

### Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- This series is UL listed under Recognized Component Index, file number E54214
- Glass passivated chip junctions
- High surge overload rating of 50 Amperes peak
- Ideal for printed circuit boards
- High temperature soldering guaranteed: 260°C/10 seconds at 5 lbs. (2.3kg) tension

### Maximum Ratings and Thermal Characteristics (T<sub>A</sub> = 25°C unless otherwise noted)

| Parameter                                                                                                         | Symbol                               | DF005S      | DF01S | DF02S | DF04S | DF06S | DF08S | DF10S | Unit               |
|-------------------------------------------------------------------------------------------------------------------|--------------------------------------|-------------|-------|-------|-------|-------|-------|-------|--------------------|
| Device marking code                                                                                               |                                      | DF005S      | DF01S | DF02S | DF04S | DF06S | DF08S | DF10S |                    |
| Maximum repetitive peak reverse voltage                                                                           | V <sub>RRM</sub>                     | 50          | 100   | 200   | 400   | 600   | 800   | 1000  | V                  |
| Maximum RMS voltage                                                                                               | V <sub>RMS</sub>                     | 35          | 70    | 140   | 280   | 420   | 560   | 700   | V                  |
| Maximum DC blocking voltage                                                                                       | V <sub>DC</sub>                      | 50          | 100   | 200   | 400   | 600   | 800   | 1000  | V                  |
| Maximum average forward output rectified current at T <sub>A</sub> = 40°C (Note 2)                                | I <sub>F(AV)</sub>                   | 1.0         |       |       |       |       |       |       | A                  |
| Peak forward surge current single half sine-wave superimposed on rated load (JEDEC Method) T <sub>J</sub> = 150°C | I <sub>FSM</sub>                     | 50          |       |       |       |       |       |       | A                  |
| Rating for fusing (t < 8.3ms)                                                                                     | I <sup>2</sup> t                     | 10          |       |       |       |       |       |       | A <sup>2</sup> sec |
| Typical thermal resistance per leg (Note 2)                                                                       | R <sub>θJA</sub><br>R <sub>θJL</sub> | 40<br>15    |       |       |       |       |       |       | °C/W               |
| Operating junction and storage temperature range                                                                  | T <sub>J</sub> , T <sub>STG</sub>    | -55 to +150 |       |       |       |       |       |       | °C                 |

### Electrical Characteristics (T<sub>A</sub> = 25°C unless otherwise noted)


|                                                             |                |     |    |
|-------------------------------------------------------------|----------------|-----|----|
| Max. instantaneous forward voltage drop per leg at 1.0A     | V <sub>F</sub> | 1.1 | V  |
| Maximum DC reverse current T <sub>A</sub> = 25°C            | I <sub>R</sub> | 5.0 | μA |
| at rated DC blocking voltage per leg T <sub>A</sub> = 125°C |                | 500 |    |
| Typical junction capacitance per leg <sup>(1)</sup>         | C <sub>J</sub> | 25  | pF |

**Notes:** (1) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts


(2) Units mounted on P.C.B. with 0.51 x 0.51" (13 x 13mm) copper pads

## Ratings and Characteristic Curves ( $T_A = 25^\circ\text{C}$ unless otherwise noted)


**Fig. 1 - Derating Curve Output Rectified Current**




**Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current Per Leg**




**Fig. 3 - Typical Forward Characteristics Per Leg**




**Fig. 4 - Typical Reverse Leakage Characteristics Per Leg**



**Fig. 5 - Typical Junction Capacitance Per Leg**



**Fig. 6 - Typical Transient Thermal Impedance**



This datasheet has been download from:

[www.datasheetcatalog.com](http://www.datasheetcatalog.com)

Datasheets for electronics components.