




# TR BF423;CEMI;TO92;tranzystor; PNP;20mA;250V;830mW;60MHz



## Dane techniczne:

Nazwa: BF423

Typ tranzystora: bipolarny

Kierunek przewodnictwa: PNP

Prąd kolektora: 20mA

Napięcie kolektor-emiter: 250V

Moc: 830mW

Częstotliwość: 60MHz

Montaż: przewlekany(THT)

Obudowa: TO92

Producent: CEMI

# BF421, BF423

## High Voltage Transistors

### PNP Silicon

#### Features

- Pb-Free Packages are Available\*

#### MAXIMUM RATINGS

Rating	Symbol	BF421	BF423	Unit
Collector–Emitter Voltage	$V_{CEO}$	-300	-250	Vdc
Collector–Base Voltage	$V_{CBO}$	-300	-250	Vdc
Emitter–Base Voltage	$V_{EBO}$	-5.0		Vdc
Collector Current – Continuous	$I_C$	-50		mAdc
Collector Current – Peak	$I_{CM}$	100		mA
Total Device Dissipation (Note 1) @ $T_A = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	830 6.6		mW mW/°C
Operating and Storage Junction Temperature Range	$T_J, T_{stg}$	-55 to +150		°C

#### THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction–to–Ambient	$R_{\theta JA}$	150	°C/W
Thermal Resistance, Junction–to–Lead	$R_{\theta JL}$	68	°C/W


Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

- Mounted on a FR4 board with 200 mm<sup>2</sup> of 1 oz copper and lead length of 5 mm.




ON Semiconductor®


<http://onsemi.com>



#### MARKING DIAGRAM



TO-92  
CASE 29  
STYLE 14



BF42x = Device Code  
x = 1 or 3  
A = Assembly Location  
Y = Year  
WW = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

#### ORDERING INFORMATION

Device	Package	Shipping
BF421ZL1	TO-92	2000/Ammo Pack
BF421ZL1G	TO-92 (Pb-Free)	2000/Ammo Pack
BF423	TO-92	5000 Units/Box
BF423G	TO-92 (Pb-Free)	5000 Units/Box
BF423ZL1	TO-92	2000/Ammo Pack
BF423ZL1G	TO-92 (Pb-Free)	2000/Ammo Pack

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# BF421, BF423

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit	
<b>OFF CHARACTERISTICS</b>					
Collector–Emitter Breakdown Voltage (Note 1) (I <sub>C</sub> = -1.0 mA, I <sub>B</sub> = 0)	BF421 BF423	V <sub>(BR)CEO</sub>	-300 -250	- -	Vdc
Collector–Base Breakdown Voltage (I <sub>C</sub> = -100 μA, I <sub>E</sub> = 0)	BF421 BF423	V <sub>(BR)CBO</sub>	-300 -250	- -	Vdc
Emitter–Base Breakdown Voltage (I <sub>E</sub> = -100 μA, I <sub>C</sub> = 0)	BF421 BF423	V <sub>(BR)EBO</sub>	-5.0 -5.0	- -	Vdc
Collector Cutoff Current (V <sub>CB</sub> = -200 Vdc, I <sub>E</sub> = 0)	BF421 BF423	I <sub>CBO</sub>	- -	-0.01 -	μA <sub>dc</sub>
Emitter Cutoff Current (V <sub>EB</sub> = -5.0 Vdc, I <sub>C</sub> = 0)	BF421 BF423	I <sub>EBO</sub>	- -	-100 -	nA <sub>dc</sub>
<b>ON CHARACTERISTICS</b>					
DC Current Gain (I <sub>C</sub> = -25 mA, V <sub>CE</sub> = -20 Vdc)	BF421 BF423	h <sub>FE</sub>	50 50	- -	-
Collector–Emitter Saturation Voltage (I <sub>C</sub> = -20 mA, I <sub>B</sub> = -2.0 mA)		V <sub>CE(sat)</sub>	-	-0.5	Vdc
Base–Emitter Saturation Voltage (I <sub>C</sub> = -20 mA, I <sub>B</sub> = -2.0 mA)		V <sub>BE(sat)</sub>	-	-2.0	Vdc
<b>SMALL–SIGNAL CHARACTERISTICS</b>					
Current–Gain – Bandwidth Product (I <sub>C</sub> = -10 mA, V <sub>CE</sub> = -10 Vdc, f = 20 MHz)		f <sub>T</sub>	60	-	MHz
Common Emitter Feedback Capacitance (V <sub>CB</sub> = -30 Vdc, I <sub>E</sub> = 0, f = 1.0 MHz)		C <sub>re</sub>	-	2.8	pF

1. Pulse Test: Pulse Width ≤ 300 μs; Duty Cycle ≤ 2.0%.

# BF421, BF423




Figure 1. DC Current Gain




Figure 2. Capacitance




Figure 3. Current-Gain - Bandwidth






Figure 4. "ON" Voltages

- $V_{CE(sat)}$  @ 25°C,  $I_C/I_B = 10$
- $V_{CE(sat)}$  @ 125°C,  $I_C/I_B = 10$
- $V_{CE(sat)}$  @ -55°C,  $I_C/I_B = 10$
- $V_{BE(sat)}$  @ 25°C,  $I_C/I_B = 10$
- $V_{BE(sat)}$  @ 125°C,  $I_C/I_B = 10$
- $V_{BE(sat)}$  @ -55°C,  $I_C/I_B = 10$
- $V_{BE(on)}$  @ 25°C,  $V_{CE} = 10$  V
- $V_{BE(on)}$  @ 125°C,  $V_{CE} = 10$  V
- $V_{BE(on)}$  @ -55°C,  $V_{CE} = 10$  V

# BF421, BF423

## PACKAGE DIMENSIONS

TO-92  
(TO-226)  
CASE 029-11  
ISSUE AL



**NOTES:**

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---

**STYLE 14:**

1. EMITTER
2. COLLECTOR
3. BASE

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

**PUBLICATION ORDERING INFORMATION**

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA  
**Phone:** 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
**Email:** orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free USA/Canada

**Japan:** ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
**Phone:** 81-3-5773-3850

**ON Semiconductor Website:** <http://onsemi.com>

**Order Literature:** <http://www.onsemi.com/litorder>

For additional information, please contact your local Sales Representative.