

**Adapter; Amass; 26.455.2; czarny; (M/F) wtyk bananowy 4mm ;  
banan; gniazdo bananowe 2mm; RoHS;**



ROBERT STĘPIEŃ  
HURTOWNIA CZĘŚCI ELEKTRONICZNYCH  
podzespoly-elektroniczne.pl

#### **Informacje ogólne:**

- Nazwa: Adapter
- Producent: Amass
- **Symbol: 26.455.2**
- Kolor izolacji: czarny

#### **Dane techniczne:**

- Prąd znamionowy: 10A
- Znamionowe napięcie: 30Vac lub 60Vdc
- Materiał styku: mosiądz niklowany
- Materiał izolacji: PA – poliamid
- Certyfikaty: RoHS




#### **Parametry fizyczne:**

- Długość całkowita: 51,5mm
- Typ adaptera: (M/F) wtyk bananowy 4mm / gniazdo bananowe 2mm

26.450.\*




**Material**  
Insulator:PA  
Body:Brass  
Surface:Nickel plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.36A



26.451.\*




**Material**  
Insulator:PA  
Body:Brass  
Surface:Nickel plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.36A



26.452.\*



**Material**  
Insulator:PA  
Body:Brass  
Spring:Beryllium copper  
Surface:Gold plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.36A



26.453.\*




**Material**  
Insulator:PA  
Body:Brass  
Spring:Beryllium copper  
Surface:Gold plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.10A



26.454.\*




**Material**  
Insulator:PA  
Body:Brass  
Surface:Nickel plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.10A



26.455.\*




**Material**  
Insulator:PA  
Body:Brass  
Spring:Beryllium copper  
Surface:Nickel plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.10A



26.456.\*



**Material**  
Insulator:PA  
Body:Brass  
Spring:Beryllium copper  
Surface:Nickel plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.10A



26.457




**Material**  
Insulator:PA  
Body:Brass  
Spring:Beryllium copper  
Surface:Nickel plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.10A



26.458.\*



**Material**  
Insulator:PA  
Body:Brass  
Spring:Beryllium copper  
Surface:Nickel plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.36A



26.459.\*




**Material**  
Insulator:PA  
Body:Brass  
Spring:Beryllium copper  
Surface:Nickel plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.36A




26.470.\*




**Material**  
Insulator:PA  
Body:Brass  
Surface:Nickel plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.10A



26.480



26.481



**Material**  
Body:Brass  
Surface:Gold plated  
**Rated voltage/current**  
30Vac-60Vdc/Max.32A